

SECTION 328400
PLANTING IRRIGATION

PART 1 - GENERAL

1.1 DESCRIPTION

A. The work in this section consists of furnishing, layout and installing an irrigation system complete, including certification of irrigation system installation as required by the State of California Model Water Ordinance described herein.

1.2 CITY REQUIREMENTS

A. CONTRACTOR shall be familiar with and follow the City or Municipality's Efficient Water Landscape Ordinance Requirements.

B. Coordination with City's Public Works Department

1. A minimum of 11 weeks prior to need for service connection, CONTRACTOR shall contact the City's Public Works Department to establish a start date to install the new water service lateral and the irrigation water meter.
2. The City will install service lateral from the water main in the street to the location shown on the plans, including the meter box. City will supply and install the irrigation meter.

3. It is the responsibility of the Contractor to furnish and install an approved Reduced Pressure Principle (RPP) type backflow prevention assembly on General Metered Service. This assembly must be installed above ground immediately following the service connection. Any deviation from the locations indicated must be approved in advance by the City Public Works Department. City requires all backflow devices to be lead free and the backflow model is to be as specified on the plans, or approved equal.

4. The RPP assembly must be installed and tested by the City before allowing water use through its services. 24 hours prior to initiating service you must contact the City Public Works Department and they will perform a field inspection and test.

1.3 QUALITY ASSURANCE

A. Manufacturer's Specifications: Follow manufacturer's current printed specifications and drawings in all cases where the manufacturers of articles used in the Contract furnish directions covering points not specified or shown in the drawings.

B. Ordinances and Regulations: All local, municipal and state laws, codes and regulations governing or relating to all portions of this work are hereby incorporated into and made a part of these Specifications. Anything contained in these Specifications shall not be construed to conflict with any of the above codes, regulations or requirements of the same. However, when these Specifications and Drawings call for or describe materials, workmanship or construction of a better quality, higher standard, or larger size than is required by the above codes and regulations, the provisions of these Specifications and Drawings shall take precedence. Furnish without extra charge additional materials and labor required to comply with above rules and regulations.

C. References, Codes and Standards:

1. City Municipal Codes
2. California Environmental Quality Act (CEQA)
3. Water Use Classification of Landscape Species (WUCOLS).
4. American Society of Irrigation Consultants (ASIC) Design Guidelines.
5. California Landscape Standards, California Landscape Contractors Association, (CLCA) Sacramento, California.
6. CAL-OSHA, title 8, Subchapter 4-Construction Safety Orders and Subchapter 7-General Industry Safety Orders.
7. California Electric Code.
8. California Plumbing Code (UPC) published by the Association of Western Plumbing Officials.
9. NFPA 24, Section 10.4, Depth of Cover.
10. Underwriters Laboratories (UL): Electrical wiring, controls, motors and devices, UL listed and so labeled.
11. American Society of Testing Materials (ASTM).

D. Furnish without extra charge any additional material and labor when required by the compliance with all above mentioned codes and regulations, though the work is not mentioned in these specifications or shown on the drawings.

E. Experience: Assign a full-time employee to the job as supervisor for the duration of the Contract with a certified landscape technician, irrigation certification through CLCA or minimum of four (4) years experience in landscape irrigation installation.

F. Labor Force: Provide a landscape installation and maintenance force thoroughly familiar with, and trained in, the work to be accomplished to perform the task in a competent, efficient manner acceptable to the ENGINEER.

G. Explanation of Drawings:

1. Due to the scale of the Drawings, it is not possible to indicate all piping offsets, fittings, sleeves, etc., which may be required. Carefully investigate the conditions affected all of the work and plan accordingly and furnish all required fittings. Install system in such a manner to avoid conflicts with planting, utilities and architectural features.

2. Do not install the irrigation system as shown on the Drawings when it is obvious in the field that obstructions, grade differences or discrepancies in area dimensions exist that might not have been considered in engineering. Bring such obstruction or differences to the attention of the ENGINEER. In the event this notification is not given, the CONTRACTOR shall assume full responsibility for any revision necessary.

H. Trench Interference with Tree Root Systems:

1. Prior to trenching, layout main and lateral line locations within Drip Line of trees and review locations with ENGINEER. Relocate any lines that may interfere with existing root systems to avoid or reduce damage to root systems as accepted by ENGINEER.

2. Mechanical Trenching is not allowed within drip line of existing trees to be protected except as approved by

ENGINEER.

I. Coordinate plant locations with emitter locations.

1. Adjust plant locations in relation to the subsurface emitters as required to ensure that the plant roots receive the proper amount of water in order for it to thrive.
2. Coordinate planting and irrigation and provide hand watering of emitter irrigated and drip irrigated areas as required to maintain moist root zones until end of plant establishment period.

1.4 PROTECTION OF EXISTING STRUCTURES AND UTILITIES

A. The Drawings show, if applicable, existing above and below grade structures and utilities that are known to the OWNER. Locate known existing installations before proceeding with construction operations that may cause damage to such installations. Existing installations shall be kept in service where possible and damage to them shall be repaired with no adjustment of Contract Sum.

B. If other structures or utilities are encountered, request ENGINEER to provide direction on how to proceed with the Work. If a structure or utility is damaged, take appropriate action to ensure the safety of persons and property.

C. CONTRACTOR to ensure that existing irrigation systems, mainline water sources are protected. Maintain irrigation to existing plants served by the existing irrigation system(s). Maintain electrical low voltage conductor connections from the existing irrigation controllers to remote control valves serving existing irrigation systems within and beyond the project limits. CONTRACTOR shall be fully responsible for all repairs to existing irrigation system(s) if a list of deficiencies is not done prior to the start of construction operations and submitted to the ENGINEER.

1.5 SUBMITTALS

A. Materials List:

1. Submit required copies of the cut sheets and a complete list of materials proposed for installation, along with any proposed substitutions clearly identified and obtain the ENGINEER's written approval thereof before proceeding. Use only accepted materials and items of equipment.

2. List all materials by manufacturer's name and model number.

B. Substitutions:

1. If the CONTRACTOR desires to substitute a product, he shall list each item and note it as a "substitution" and provide the following information:
 - a. Descriptive information describing its similarities to the specified product.
2. If the product is approved and, in the opinion of the ENGINEER, the substituted product does not perform as well as the specified product, the CONTRACTOR shall replace it with the specified product at no additional cost to the OWNER.

C. Operations and Maintenance Manuals:

1. Prior to the final acceptance of the irrigation system, furnish three (3) individually bound Operation and Maintenance Manuals to the ENGINEER for use by the OWNER. The manuals shall contain complete enlarged drawings, diagrams and spare parts lists of all equipment installed showing manufacturer's name and address. In addition, each Service Manual shall contain the following:
 - a. Index sheet indicating the CONTRACTOR's name, address and phone number.
 - b. Copy of the Landscape Irrigation Audit
 - c. Copy of the 12-month irrigation schedule and estimate of annual water consumption.
 - d. Copies of equipment warranties and certificates.
 - e. List of equipment with names, addresses and telephone numbers of all local manufacturer representatives.
 - f. Complete operating and maintenance instructions in sufficient detail to permit operating personnel to understand, operate and maintain all equipment.
 - g. Parts list of all equipment such as controllers, valves, solenoids and heads.

D. Record Drawings:

1. Dimension the location of the following items from two (2) permanent points of reference such as building corners, sidewalks, road intersections, etc.:

- a. Connection to existing water lines/meter.
- b. Connection to electrical power.
- c. Gate valves.
- d. Routing of sprinkler pressure lines (a dimension at least every 100 feet and as required to identify all changes in direction and location).
- e. Remote control valves.
- f. Routing of control valves.
- g. Quick coupling valves.
- h. All sleeve locations.
- i. Routing of all control wiring.
- j. Include all invert elevations below 12'.

2. Deliver a reproducible record drawing to the ENGINEER within seven (7) working days before the date of final review. Delivery of the record drawings shall not relieve the CONTRACTOR of the responsibility of furnishing required information in the future.

E. Controller Plan:

1. Provide one Irrigation Diagram plan in each controller housing. The plan shall show the area controlled by each valve in different colors and for orientation, any major permanent structure such as buildings and roads.
2. Charts to be waterproof and hermetically sealed between two pieces of transparent 10 mil thick plastic and installed in each controller on the door as accepted by the ENGINEER no later than the time of the coverage test of the irrigation system.

F. Maintenance Material - supply the following tools to the OWNER:

1. Three (3) sets of specialized tools required for removing, disassembling and adjusting each type of sprinkler, valve or other equipment supplied on this project.

2. Two (2) keys for each type of equipment enclosure.

3. Two (2) keys for each type of automatic controller.

4. Two (2) keys for each type of valve (including square type key for valves larger than 2")

5. Two (2) quick-coupler keys and matching hose swivels for each type of quick-coupling valve installed.

6. All lock keys shall be keyed alike.

F. Irrigation Inspection Checklist - supply the attached checklist to the OWNER upon completion.

1.6 PRODUCT DELIVERY, STORAGE AND HANDLING

A. Furnish and deliver materials in manufacturer's packaging, bearing original legible labeling.

B. The CONTRACTOR is cautioned to exercise care in handling, loading, unloading, and storing PVC pipe and fittings. All PVC pipe shall be transported in a vehicle which allows the length of the pipe to lie flat so as not to subject it to undue bending or concentrated external load at any point. Any section of pipe that has been dented, cracked, or otherwise damaged shall be discarded and, if installed, shall be replaced with new piping.

1.7 TRENCH INTERFERENCE WITH TREE ROOT SYSTEMS

- A. Prior to trenching, layout main and lateral line locations within Drip Line of trees and review locations with ENGINEER. Relocate any lines that may interfere with existing root systems to avoid or reduce damage to root systems as accepted by ENGINEER.

1.8 SEQUENCING AND SCHEDULING

A. Acceptance: Do not install main line trenching prior to acceptance by ENGINEER of rough grades completed under another Section.

B. Coordination: Coordinate with the work of other sections to insure the following sequence of events:

1. Sleeves and Conduits: Installation of all sleeves and conduits to be located under paving and through walls prior to placement of those materials.
2. Stream Bubbler Heads: Install after placement of tree, but prior to backfill with planter soil mix.
3. Coordinate work schedule with OWNER to avoid disruption of landscape maintenance of existing landscaping.
4. Install piping prior to soil preparation (planting soil amendment installation).

1.9 WARRANTY

A. In addition to manufacturer's guarantees and warranties, work shall be warranted for one (1) year from date of final acceptance against defects in material, equipment and workmanship. Warranty shall also cover repair of damage to any of the premises resulting from leaks or other defects in materials, equipment and workmanship to the satisfaction of the OWNER.

B. Include a copy of the warranty form in the Operation and Maintenance Manual.

1.10 OPERATION

- A. Routine: Inspect and adjust all spray heads and control valves including raising or lowering of spray head heights to accommodate plant growth and weather conditions.
- B. Controller: Inspect regularly for power interruption and reset clock as required. Adjust station timing to accommodate changes in plant growth and weather conditions.
- C. System Failure: Perform all repairs within one (1) operating period. Replacements to match removed products and materials in all respects. Report promptly all damage not resulting from CONTRACTOR's operations. Repair all damage caused by CONTRACTOR at no expense to OWNER.
- D. Climate Change: Set and program automatic controllers in response to seasonal requirements and requirements of newly planted materials.

PART 2 - PRODUCTS

2.1 PIPE

A. Pressure Main Line Pipe and Fittings: All PVC fittings shall bear the manufacturer's trademark name, material designation, size, applicable I.P.S. schedule and NSF seal of approval.

B. All main line pipe shall be solvent welded and shall be schedule 40 unless shown otherwise on the Drawings.

1. PVC Pressure Rated Pipe: ASTM D2241 NSF approved Type I, Grade I, solvent welded PVC with an appropriate standard dimension ratio (S.D.R.).

2. PVC Scheduled Pipe: ASTM D1785 NSF approved, Type I.

3. Grade I, solvent welded PVC.

4. PVC Solvent-weld Fittings: ASTM D2466 Schedule 40, 1-2, 1/4 NSF approved.

5. Solvent Cement and Primer for PVC solvent-weld pipe and fittings: Type and installation methods prescribed by the manufacturer.

6. Connections between Main Lines and RCVs: Schedule 80 PVC threaded (both ends) nipples and fittings unless required otherwise by local jurisdiction

7. Valves 2-inch and larger shall be flanged only.

8. Copper pipe shall be Type K or Red Brass where threaded joints are required and Type L otherwise.

E. Provide polyurethane tag at valve solenoid control wire that

C. All lateral line pipe shall be solvent welded and shall be schedule 40 unless shown otherwise on the Drawings.

2.2 CONTROLLER ENCLOSURES

A. Type: As shown on plans (or approved equal)

2.3 REMOTE CONTROL VALVE: As shown on Drawings and with the following minimum requirements:

A. Remote control valves shall be those normally manufactured for irrigation systems and shall have a slow, consistent speed of closure through entire closing operation, including last portion. To ensure this, the effective diaphragm working area/valve seating opening ratio must be a minimum 3 to 1.

B. Shall be mechanically self-cleaning to help prevent diaphragm or solenoid port plugging. To ensure this, the flush rod should be tapered to vary the size of the port opening as the diaphragm raises and lowers, thus allowing trapped material to escape. Rod is to be finished with a serrated surface to help scrub trapped material out. Screens not acceptable.

C. Shall have removable valve seat so valve can be repaired without removal from irrigation line.

D. Shall have ability to operate manually without the use of wrenches or special keys.

E. Shall have one-piece solenoid that attaches directly to valve without shunts or clips that can be lost.

F. Shall have cross top handle to adjust maximum travel of diaphragm to allow "tuning" of valve and closure.

2.4 BOX FOR REMOTE CONTROL VALVE

A. Valve boxes shall be rated for an h=20 traffic Loading or conform to ASTM D-638, tensile strength 3400 psi and impact Strength of 1.5 pounds per inch. Valve box extensions shall be of the Same type as the valve box and all covers shall be lockable and be Minimum overall size of 13" x 24" and minimum depth of 24".

2.5 CONTROLLER GROUND

A. Provide each pedestal controller with its own ground rod. Separate the ground rods by a minimum of eight feet. The ground rod shall be an eight foot long by 5/8" diameter U.L. approved copper clad rod or as recommended by controller manufacturer. Install no more than 6" of the ground rod above finish grade. Connect #8 gauge wire with a U.L. approved ground rod clamp to rod and back to ground screw at base of controller with appropriate connector. Make this wire as short as possible, avoiding any kinks or bending. Install within pedestal housing base unless otherwise noted.

B. Provide each irrigation controller with its own independent low voltage common ground wire.

2.6 GENERAL REQUIREMENTS FOR AUTOMATIC CONTROLLERS & CENTRAL:

A. Satellite Controllers: Capable of operating with manufacturer's Central Control System software.

B. Flow Sensors: Compatible with Central Control System and as recommended by Control System manufacturer.

C. Flow Monitors: Compatible with Central Control System and as recommended by manufacturer.

D. Hand Held Remote Control: Portable device as manufactured by Control System manufacturer capable of operating all control valves.

E. Master Control Valve: Master control valve shall be a 24 VAC, industrial type, solenoid control valve, Griswold 2000 series or equal. Valve shall be equipped with spring loaded packless diaphragm, cast iron body and bronze trim. The valve shall be of the normally closed type and shall be equipped with four-prong (cross) flow control. Valve shall be slow closing without chatter settings or adjustment. Valve shall have a mechanical self-purging internal control system with tapered, serrated, scrubbing rod through diaphragm for positive, variable port opening and cleaning. No solenoid port screens. Valve solenoid shall be corrosion-proof, molded in epoxy to form one integral unit with no connection shunts and shall be 24 VAC, 3 watt maximum.

F. Controller Ground:

1. Provide each pedestal controller with its own ground rod set remote from controller as recommended by controller manufacturer. Separate the ground rod by a minimum of eight feet. The ground rod shall be an eight foot long by 5/8" diameter U.L. approved copper clad rod or as recommended by controller manufacturer. Install no more than 6" of the ground rod above finish grade. Connect #8 gauge wire with a U.L. approved ground rod clamp to rod and back to ground screw at base of controller with appropriate connector. Make this wire as short as possible, avoiding any kinks or bending. Install within pedestal housing base unless otherwise noted.

2. Provide each irrigation controller with its own independent low voltage common ground wire.

2.7 CONTROL WIRES

A. Connections between automatic controllers and the solenoid-operated electric control valves shall be made with direct burial copper wire 14- AWG-UF 600 volt (minimum size). Pilot wires shall be a color other than white, and shall be a different color for each automatic controller with wires sharing a common trench. Common wires shall be white in color, with a different color stripe for each controller with wiring sharing the same common trench. No stripe is required if multiple controller wiring is not present.

B. Size of wire shall conform to the remote control valve manufacturer's specification for control wire sizes, but in no case shall the control wire be smaller than #14. Runs over 2,000 lineal feet shall be #12- AWG-UF 600 volt copper wire.

C. Stub-outs: Verify that all stub-outs to be provided under another contract are correctly sized, located and installed as noted on Drawings.

D. Notification: Submit written notification to ENGINEER within ten (10) working days of above inspections describing all acceptable and non-acceptable site conditions. Technical Specifications invitation for Bids No. PW15-11

3.2 TRENCH INTERFERENCE WITH TREE ROOT SYSTEMS:

A. Prior to trenching, layout main and lateral line locations within Drip Line of trees and review locations with ENGINEER. Relocate any lines that may interfere with existing root systems to avoid or reduce damage to root systems as accepted by ENGINEER.

A. Provide and coordinate connection to water meter.

B. Provide and coordinate connection of irrigation controller to electrical power source.

shows the controller number and station number. Also refer to valve box lid identification.

F. Provide a spare control wire in each RCV box for future.

2.8 SHRUB POP UP SPRAY HEAD

A. As shown on drawings (or approved equal)

2.9 QUICK COUPLER VALVES:

A. Quick coupler valves shall be as listed on the Drawings with 10" diameter box and lid similar to isolation valve box described below.

2.10 ISOLATION VALVE:

A. Valves 3 inches and smaller: 125 lb. WSP bronze gate valve with screw-in bonnet, non-rising stem and solid wedge disc, NIBCO T-580-A (or approved equal). Valves shall be line size.

2.11 BOX FOR ISOLATION VALVE

A. 10" diameter plastic, Ametek, Brooks, Christy, Rain Bird with bolt down lid marked "irrigation," or accepted equal. Avoid locating valve in paved areas. Provide H2O Loading concrete box with bolt-down concrete lid if valve is located in paved area. Obtain location approval by ENGINEER.

2.12 SWING JOINTS

A. Sprinklers and Bubbler: Use Dura, Lasco, Rain Bird or equal pre-assembled swing joints with O-rings.

B. Quick Coupling Valve: Dura 1-inch 1-A2-11-18 pre-assembled swing joint with O-rings and Dura quick lock to prevent stabilizing rod.

2.13 BACKFLOW PREVENTION DEVICE

A. As required by Code and as shown on Drawings. Provide an Anti-freeze Jacket.

B. Riser assemblies from main line burial depth to backflow preventers shall be Schedule 40 brass pipe.

C. All metallic pipe and fittings installed below grade shall be painted with two coats of Koppers #50 Bitumastic, or approved equal. Pipes may be wrapped with an approved asphaltic tape in lieu of the liquid-applied coating.

D. Backflow preventer shall receive a minimum 6 inch thick concrete coordinated to fit backflow preventer enclosure as shown and as accepted by the ENGINEER.

2.14 BACKFLOW PREVENTION DEVICE ENCLOSURE - As shown on the drawings

2.15 CONDUIT/SLEEVES

A. Sleeving shall be Schedule 40 PVC pipe sleeves and a minimum of two times the aggregate diameter of all pipes contained within the sleeve. Provide vertical sweep for all electrical conduit on each side of hardscape and terminate ends at 12" minimum depth and 12" from hardscape surface.

2.16 RCV IDENTIFICATION TAGS: Plastic or brass tags with valve number, approximately 2" by 2" with number imprinted, as accepted by OWNER.

2.17 MISCELLANEOUS INSTALLATION MATERIALS

A. Solvent Cement and Primers for Solvent-weld Joints: Make and type approved by manufacturer(s) of pipe and fittings. Maintain cement proper consistency throughout use.

B. Pipe and Joint Compound: Permatex; Do not use on sprinkler inlet port.

2.18 MISCELLANEOUS EQUIPMENT/ACCESSORIES

A. Concrete for equipment pads: Poured-in-place Class A concrete per Section 50 of the Caltrans Standard Specifications.

B. Sleeves and Conduits: See Drawings.

C. Keys(s) for Quick-Coupling Valves:

1. Type: Same manufacturer as Quick-Coupling Valve.

2.26 OTHER EQUIPMENT: As shown on Drawings and required for a fully functional irrigation system.

PART 3 - EXECUTION

3.1 EXAMINATION

A. Sleeves and Conduits: Verify that all installed sleeving and conduits are undisturbed and are free of defects or errors introduced by the work of other sections.

B. Water Meter/Water Pressure: Test and verify that existing water pressure is the minimum pressure at maximum system g.p.m. to operate the irrigation system as indicated on the drawings.

C. Stub-outs: Verify that all stub-outs to be provided under another contract are correctly sized, located and installed as noted on Drawings.

D. Notification: Submit written notification to ENGINEER within ten (10) working days of above inspections describing all acceptable and non-acceptable site conditions. Technical Specifications invitation for Bids No. PW15-11

3.2 TRENCH INTERFERENCE WITH TREE ROOT SYSTEMS:

A. Prior to trenching, layout main and lateral line locations within Drip Line of trees and review locations with ENGINEER. Relocate any lines that may interfere with existing root systems to avoid or reduce damage to root systems as accepted by ENGINEER.

3.3 CONNECTIONS TO SERVICES

A. Provide and coordinate connection to water meter.

B. Provide and coordinate connection of irrigation controller to electrical power source.

3.4 INSTALLATION

A. Install Irrigation system components in accordance with this Section, with the Drawings, with the manufacturer's recommendations, and with established industry standards. The CONTRACTOR shall do nothing that may jeopardize any manufacturer warranty.

B. Conduits and Sleeves:

1. Coordination: Provide conduits and sleeves and coordinate installation with other trades.

2. Extent: Install conduits and sleeves where control wires and pipes pass under paving or through walls as shown on Drawings. Extend twelve inches (12") beyond edges of paving and walls and cap ends until ready for use.

C. Excavating and Trenching:

1. Pipe Layout: Layout pipe lines within Spread of Tree Branches as described above in Section 1.7, TRENCH INTERFERENCE WITH TREE ROOT SYSTEMS.

2. Dig trenches wide enough to allow a minimum of three inches (3") between parallel pipe lines. Provide a minimum cover from finish grade as follows:

D. Pipeline Assembly:

1. Install pipe and fittings in accordance with manufacturer's current printed Specifications.

2. Clean all pipes and fittings of dirt, scale and moisture before assembly.

3. Solvent-welded Joints for PVC Pipes:

a. Solvents: Use solvents and methods specified by pipe manufacturer.

b. Curing Period: Minimum of one (1) hour before applying any external stress on the piping and at least 24 hours before placing the joint under water pressure.

4. Threaded Joints for Plastic Pipes:

a. Use Permatex on all threaded PVC fittings except sprinkler heads and quick coupler valve ACME threads.

b. Joining: Use strap-type friction wrench only. Do not use metal-jawed wrench.

Assemble finger tight plus one or two turns.

5. Laying of Pipe:

a. Bedding On-grade: Remove from trench all rocks or clods. Bed pipe in at least 2 inches of soil excavated from trench. Backfill on all sides of piping to provide a uniform bearing.

b. Snaking: Snake pipe from side to side of trench bottom to allow for expansion and contraction. Minimum allowance for snaking is one (1) additional foot per 100 ft. of pipe.

c. Moisture Restrictions: Do not lay PVC pipe when there is water in the trench. Do not assemble PVC pipe unless the pipe is dry.

E. Control Valves:

1. Install in valve boxes where shown on Drawings and group together where practical. Install box flush with finish grade, not necessarily level. If valve occurs in drainage swale, relocate out of drainage swale as approved by ENGINEER.

2. Where two or more valves are installed adjacent to each other, provide at least six inches (6") separation. Align boxes in a row, perpendicular with pavement edge.

3. Permanently mark valve box lid with 2" black valve number and controller letter or with numbered metal tag inside box as approved by ENGINEER.

4. Refer to control wiring for required spare wire in each valve box.

F. Sprinkler Head Installation:

1.1. Coordinate installation with planting CONTRACTOR to insure timely and proper placement of heads at new planting.

G. Automatic Controller:

1. General: Install with lock box cutoff switch per local code and manufacturer's current printed specifications.

2. Connection to Valves: Connect remote control valves to controller in clockwise sequence to correspond with station setting beginning with Stations 1, 2, 3, etc.

3. Labeling: Affix controller letter (i.e., "A") on inside of controller cabinet door with minimum of one-inch (1") high permanent letter.

4. Irrigation Diagram: Affix a non-fading, waterproof copy of irrigation diagram to cabinet door below controller name. Irrigation diagram to be sealed between two plastic sheets, 20 mil. minimum thickness. Use a legible reduced copy of the Record Drawing for the irrigation diagram clearly showing all valves operated by the controller, station number, valve size, and type of planting irrigated. Color code area operated by each valve.

H. Control Wiring:

1. General: Install control wires in common trenches with sprinkler mains and laterals wherever possible. Lay to