



**STANDARD SEDIMENT FENCE**

**FRONT VIEW**  
NTH

**TOP VIEW**  
NTH

**SEDIMENT FENCE WITH ROCK CHECK DAM**

**FRONT VIEW**  
NTH

**SIDE VIEW**  
NTH

**NOTES:**

1. FILTER FABRIC MUST BE PURCHASED IN A CONTINUOUS ROLL CUT TO LENGTH OF THE BARRIER TO AVOID USE OF JOINTS. WHEN JOINTS ARE NECESSARY, FILTER CLOTH SHALL BE SPLICED TOGETHER ONLY AT A SUPPORT POST, WITH A MINIMUM 6-INCH OVERLAP. BOTH ENDS SHALL BE SECURELY FASTENED TO THE POST OR OVERLAPPED AS SHOWN.
2. THE FILTER FABRIC FENCE SHALL BE INSTALLED TO FOLLOW THE CONTOURS WHERE FEASIBLE. THE FENCE POSTS SHALL BE SPACED A MAXIMUM OF 8 FEET APART AND DRIVEN INTO THE GROUND A MINIMUM OF 18 INCHES.
3. THE FILTER FABRIC SHALL HAVE A MINIMUM VERTICAL BURIAL OF 8 INCHES. ALL EXCAVATED MATERIAL FROM THE FENCE INSTALLATION SHALL BE BACKFILLED AND COMPACTED ALONG THE ENTIRE UP HILL SIDE OF THE DISTURBED AREA.
4. STANDARD HEAVY DUTY FILTER FABRIC FENCE SHALL HAVE MANUFACTURED STITCHED LOOPS FOR 2"x2" POST INSTALLATION. STITCHED LOOPS SHALL BE INSTALLED ON THE UP HILL SIDE OF THE SLOPED AREA.
5. FILTER FABRIC FENCES SHALL BE REMOVED WHEN THEY HAVE SERVED THEIR USEFUL PURPOSE, BUT NOT BEFORE THE UPSLOPE AREA HAS BEEN PERMANENTLY PROTECTED, STABILIZED, AND APPROVED BY THE CITY.
6. REMOVE ACCUMULATED SEDIMENT MATERIAL ONCE IT HAS REACHED WITHIN 18 INCHES OF THE TOP OF THE SEDIMENT FENCE.