



- 1. TCLL-TCDL-BCLL-BCDL: 25-7-0-10 (U.N.O)
- 2. Roof slope: 5/12, Heel:2x4, Tails: 16"
- 3. 24" o.c spacing (U.N.O)
- 4. Dimensions to outside of building (U.N.O)
- 5. Trusses may be shifted in field as req'd without exceeding max truss spacing.



P.O. Box 5787 17900 SE Wallace Rd Dayton, OR 97114 Tel: (503) 581-8787 Fax: (503) 399-8787

Rachel/ Better Built Barns 38x50

Project Number

3867 37th Ave

2505127CIA

Customer:

Designer:

Cash in Advance

Dillon Pickles

Salesperson ID:

Tami Heath

Revision 1:

Date: 05 / 12 / 25

THIS IS A TRUSS PLACEMENT DIAGRAM ONLY

These trusses are designed as individual building components to be incorporated into the building design at the specification of the building designer. See individual design sheets for each truss design identified on the placement drawing. The building designer is responsible for temporary and permanent bracing of the roof and floor system and for the overall structure. The design of the entire truss support structure including, but not limited to headers, beams, walls, and columns is the responsibility of the building designer. For general guidance regarding bracing, consult "Bracing of wood trusses" available from the Truss Plate Institute, 218 N. Lee Street, Ste. 312, Alexandria, VA 22314.