

# **PRELIMINARY STORM WATER REPORT PROPOSED QUAIL SPRING VILLAGE SUBDIVISION**

**LOCATED AT:**

**430 TURTLE BAY COURT  
SALEM, OREGON 97306**



**JOB NO. 2020-21  
MARCH 11, 2021**

**PREPARED BY  
GERALD P. HORNER, PE**



REFERENCE ONLY




**SPRING QUAIL VILLAGE  
OFFSITE MAP**

1 inch = 150 feet

This product is provided as-is, without warranty. In no event is the City of Salem liable for damages from the use of this product. This product is subject to license and copyright limitations and further distribution or resale is prohibited.





STORM WATER AREAS AND PRE-DEVELOPMENT TRAVEL TIME

SCALE: 1"=50'

SPRING QUAIL VILLAGE  
PERVIOUS AND IMPERVIOUS AREAS

TOTAL SITE: 5.02 ACRES(218,881 SQUARE FEET)  
EXISTING HOUSE AND APRONS: 4,700 SQUARE FEET  
NEW STREETS: 27,750 SQUARE FEET  
14 NEW HOUSES: 14 x 2,500 SQ. FEET 35,000 SQUARE FEET  
14 NEW DRIVEWAYS: 14 x 30' x 25' 10,500 SQUARE FEET  
14 NEW PATIOS: 14 x 20' x 20' 5,600 SQUARE FEET  
SIDEWALKS: 7,250 SQUARE FEET

TRAVEL TIME ON WEST SIDE

$\frac{564' - 520'}{440'} = 10\%$   
 $T = \frac{0.93(300^6)(30^6)}{(0.82^4)(0.10)^3} = 30 \text{ MINUTES}$   
 $I = 0.82" \text{ FOR } 30 \text{ MINUTES}$

NORTH OFFSITE  
PERVIOUS AND IMPERVIOUS AREAS

TOTAL SITE: 11.90 ACRES(518,170 SQUARE FEET)  
EXISTING HOUSE AND APRONS: 3,500 SQUARE FEET  
261 SUMMERSIDE  
BRUSH AND GRASS: 514,670 SQUARE FEET

TRAVEL TIME ON NORTH OFFSITE

$\frac{596' - 540'}{525'} = 10.7\%$   
 $T = \frac{0.93(300^6)(30^6)}{(0.82^4)(0.107)^3} = 30 \text{ MINUTES}$   
 $I = 0.82" \text{ FOR } 30 \text{ MINUTES}$

SPRING QUAIL VILLAGE  
TREES

THERE ARE 21 EXISTING TREES TO BE SAVED AND AT LEAST TWO(2) TREES PLANTED PER LOT. THIS AMOUNTS TO A TOTAL POTENTIAL REDUCTION IN IMPERVIOUS AREA OF 1,610 SQUARE FEET OR 0.058 ACRES

14 LOTS - 14 x 2 x 20 SQUARE FEET = 560 SQUARE FEET.  
21 TREES x 50 SQUARE FEET PER TREE = 1,050 SQUARE FEET

FOR APPLICATION  
NOT FOR CONSTRUCTION



REV.	DATE	BY	DESCRIPTION
0	03-10-21	GPH	ISSUED FOR SUBDIVISION APPLICATION





DESIGNED BY: GPH	
DRAWN BY: RW	
DATE: 03-10-21	
JOB NO. 2020-21	
CLIENT NO.	
DRAWING NO. C6	REV. 0

ENGINEER:  
WILLAMETTE ENGINEERING INC.  
P.O. BOX 9032  
SALEM, OREGON 97305  
PH: 503-304-0905  
FAX: 503-304-9512

STORM WATER  
AREAS AND PRE-  
DEVELOPMENT TRAVEL  
TIME

SPRING QUAIL VILLAGE  
SUBDIVISION

430 TURTLE BAY CT SE  
SALEM, OREGON 97306



**20-066 Noyes Subdivision Stormwater Model**

Prepared by Branch Engineering

Printed 3/9/2021

HydroCAD® 10.00-20 s/n 09344 © 2017 HydroCAD Software Solutions LLC

Page 2

**Area Listing (all nodes)**

Area (sq-ft)	CN	Description (subcatchment-numbers)
1,029,340	79	50-75% Grass cover, Fair, HSG C (S2, X2)
7,000	98	Existing House (S2, X2)
99,640	98	Impervious (S1)
116,731	74	Pervious (S1)
216,371	72	Woods/grass comb., Good, HSG C (X1)
<b>1,469,082</b>	<b>79</b>	<b>TOTAL AREA</b>

**20-066 Noyes Subdivision Stormwater Model**

Prepared by Branch Engineering

Printed 3/9/2021

HydroCAD® 10.00-20 s/n 09344 © 2017 HydroCAD Software Solutions LLC

Page 3

**Pipe Listing (all nodes)**

Line#	Node Number	In-Invert (feet)	Out-Invert (feet)	Length (feet)	Slope (ft/ft)	n	Diam/Width (inches)	Height (inches)	Inside-Fill (inches)
1	1P	513.50	513.00	50.0	0.0100	0.011	24.0	0.0	0.0
2	UF	512.50	512.10	20.0	0.0200	0.013	24.0	0.0	0.0
3	UF	512.50	512.00	20.0	0.0250	0.011	24.0	0.0	0.0

## 20-066 Noyes Subdivision Stormwater Model

Prepared by Branch Engineering

HydroCAD® 10.00-20 s/n 09344 © 2017 HydroCAD Software Solutions LLC

20-066 Noyes Sub  
Type IA 24-hr 10 yr Rainfall=3.20"

Printed 3/9/2021

Page 4

Time span=0.00-72.00 hrs, dt=0.01 hrs, 7201 points

Runoff by SBUH method, Split Pervious/Imperv.

Reach routing by Dyn-Stor-Ind method - Pond routing by Dyn-Stor-Ind method

<b>Subcatchment S1: Subdivision</b>	Runoff Area=216,371 sf 46.05% Impervious Runoff Depth=1.93" Tc=10.0 min CN=74/98 Runoff=2.10 cfs 34,733 cf
<b>Subcatchment S2: Offsite</b>	Runoff Area=518,170 sf 0.68% Impervious Runoff Depth=1.35" Tc=30.0 min CN=79/98 Runoff=2.31 cfs 58,196 cf
<b>Subcatchment X1: Subdivision</b>	Runoff Area=216,371 sf 0.00% Impervious Runoff Depth=0.93" Tc=30.0 min CN=72/0 Runoff=0.49 cfs 16,763 cf
<b>Subcatchment X2: Offsite</b>	Runoff Area=518,170 sf 0.68% Impervious Runoff Depth=1.35" Tc=30.0 min CN=79/98 Runoff=2.31 cfs 58,196 cf
<b>Pond 1P: 60" Storage Pipe</b>	Peak Elev=517.65' Storage=13,932 cf Inflow=4.38 cfs 92,929 cf Outflow=2.76 cfs 90,026 cf
<b>Pond UF: Up-Flo</b>	Peak Elev=514.02' Storage=169 cf Inflow=2.76 cfs 90,026 cf Primary=2.48 cfs 65,896 cf Secondary=0.28 cfs 24,034 cf Outflow=2.76 cfs 89,930 cf
<b>Link POST: Post Development</b>	Inflow=2.76 cfs 89,930 cf Primary=2.76 cfs 89,930 cf
<b>Link PRE: Pre Development</b>	Inflow=2.79 cfs 74,959 cf Primary=2.79 cfs 74,959 cf
<b>Total Runoff Area = 1,469,082 sf Runoff Volume = 167,887 cf Average Runoff Depth = 1.37"</b> <b>92.74% Pervious = 1,362,442 sf 7.26% Impervious = 106,640 sf</b>	

**20-066 Noyes Subdivision Stormwater Model**

Prepared by Branch Engineering

HydroCAD® 10.00-20 s/n 09344 © 2017 HydroCAD Software Solutions LLC

20-066 Noyes Sub  
Type IA 24-hr 10 yr Rainfall=3.20"

Printed 3/9/2021

Page 5

**Summary for Subcatchment S1: Subdivision**

Runoff = 2.10 cfs @ 8.00 hrs, Volume= 34,733 cf, Depth= 1.93"

Runoff by SBUH method, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.01 hrs  
Type IA 24-hr 10 yr Rainfall=3.20"

	Area (sf)	CN	Description
*	99,640	98	Impervious
*	116,731	74	Pervious
	216,371	85	Weighted Average
	116,731	74	53.95% Pervious Area
	99,640	98	46.05% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
10.0					Direct Entry,

**Summary for Subcatchment S2: Offsite**

Runoff = 2.31 cfs @ 8.08 hrs, Volume= 58,196 cf, Depth= 1.35"

Runoff by SBUH method, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.01 hrs  
Type IA 24-hr 10 yr Rainfall=3.20"

	Area (sf)	CN	Description
	514,670	79	50-75% Grass cover, Fair, HSG C
*	3,500	98	Existing House
	518,170	79	Weighted Average
	514,670	79	99.32% Pervious Area
	3,500	98	0.68% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
30.0					Direct Entry,

**Summary for Subcatchment X1: Subdivision**

Runoff = 0.49 cfs @ 8.22 hrs, Volume= 16,763 cf, Depth= 0.93"

Runoff by SBUH method, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.01 hrs  
Type IA 24-hr 10 yr Rainfall=3.20"

	Area (sf)	CN	Description
	216,371	72	Woods/grass comb., Good, HSG C
	216,371	72	100.00% Pervious Area



**20-066 Noyes Subdivision Stormwater Model**

Prepared by Branch Engineering

HydroCAD® 10.00-20 s/n 09344 © 2017 HydroCAD Software Solutions LLC

20-066 Noyes Sub  
Type IA 24-hr 10 yr Rainfall=3.20"

Printed 3/9/2021

Page 6

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
30.0					<b>Direct Entry,</b>

**Summary for Subcatchment X2: Offsite**

Runoff = 2.31 cfs @ 8.08 hrs, Volume= 58,196 cf, Depth= 1.35"

Runoff by SBUH method, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.01 hrs  
Type IA 24-hr 10 yr Rainfall=3.20"

Area (sf)	CN	Description
514,670	79	50-75% Grass cover, Fair, HSG C
3,500	98	Existing House
518,170	79	Weighted Average
514,670	79	99.32% Pervious Area
3,500	98	0.68% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
30.0					<b>Direct Entry,</b>

**Summary for Pond 1P: 60" Storage Pipe**

Inflow Area = 734,541 sf, 14.04% Impervious, Inflow Depth = 1.52" for 10 yr event  
 Inflow = 4.38 cfs @ 8.00 hrs, Volume= 92,929 cf  
 Outflow = 2.76 cfs @ 8.75 hrs, Volume= 90,026 cf, Atten= 37%, Lag= 44.6 min  
 Primary = 2.76 cfs @ 8.75 hrs, Volume= 90,026 cf

Routing by Dyn-Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.01 hrs  
 Peak Elev= 517.65' @ 8.75 hrs Surf.Area= 3,008 sf Storage= 13,932 cf

Plug-Flow detention time= 160.8 min calculated for 90,013 cf (97% of inflow)  
 Center-of-Mass det. time= 140.6 min ( 945.1 - 804.5 )

Volume	Invert	Avail.Storage	Storage Description
#1	513.50'	15,708 cf	<b>60.0" Round Pipe Storage</b> x 4 L= 200.0'

Device	Routing	Invert	Outlet Devices
#1	Primary	513.50'	<b>24.0" Round Culvert</b> L= 50.0' Ke= 0.500 Inlet / Outlet Invert= 513.50' / 513.00' S= 0.0100 ' / Cc= 0.900 n= 0.011, Flow Area= 3.14 sf
#2	Device 1	514.70'	<b>2.0" Horiz. Half 2-yr Orifice</b> C= 0.600 Limited to weir flow at low heads
#3	Device 1	516.20'	<b>9.0" Horiz. 10-yr Orifice</b> C= 0.600 Limited to weir flow at low heads
#4	Device 1	517.60'	<b>24.0" Vert. Overflow</b> C= 0.600

## 20-066 Noyes Subdivision Stormwater Model

Prepared by Branch Engineering

HydroCAD® 10.00-20 s/n 09344 © 2017 HydroCAD Software Solutions LLC

20-066 Noyes Sub  
Type IA 24-hr 10 yr Rainfall=3.20"

Printed 3/9/2021

Page 7

**Primary OutFlow** Max=2.76 cfs @ 8.75 hrs HW=517.65' TW=514.02' (Dynamic Tailwater)

- 1=Culvert (Passes 2.76 cfs of 26.84 cfs potential flow)
- 2=Half 2-yr Orifice (Orifice Controls 0.18 cfs @ 8.27 fps)
- 3=10-yr Orifice (Orifice Controls 2.56 cfs @ 5.79 fps)
- 4=Overflow (Orifice Controls 0.01 cfs @ 0.75 fps)

### Summary for Pond UF: Up-Flo

Inflow Area = 734,541 sf, 14.04% Impervious, Inflow Depth = 1.47" for 10 yr event  
Inflow = 2.76 cfs @ 8.75 hrs, Volume= 90,026 cf  
Outflow = 2.76 cfs @ 8.75 hrs, Volume= 89,930 cf, Atten= 0%, Lag= 0.1 min  
Primary = 2.48 cfs @ 8.75 hrs, Volume= 65,896 cf  
Secondary = 0.28 cfs @ 7.70 hrs, Volume= 24,034 cf

Routing by Dyn-Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.01 hrs  
Peak Elev= 514.02' @ 8.75 hrs Surf.Area= 48 sf Storage= 169 cf

Plug-Flow detention time= 3.7 min calculated for 89,930 cf (100% of inflow)  
Center-of-Mass det. time= 1.4 min ( 946.5 - 945.1 )

Volume	Invert	Avail.Storage	Storage Description
#1	510.50'	240 cf	<b>Custom Stage Data (Prismatic)</b> Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
510.50	48	0	0
513.50	48	144	144
515.50	48	96	240

Device	Routing	Invert	Outlet Devices
#1	Primary	512.50'	<b>24.0" Round Culvert</b> L= 20.0' Ke= 0.500 Inlet / Outlet Invert= 512.50' / 512.10' S= 0.0200 '/' Cc= 0.900 n= 0.013, Flow Area= 3.14 sf
#2	Device 1	513.50'	<b>2.1' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)
#3	Secondary	512.50'	<b>24.0" Round Culvert</b> L= 20.0' Ke= 0.500 Inlet / Outlet Invert= 512.50' / 512.00' S= 0.0250 '/' Cc= 0.900 n= 0.011, Flow Area= 3.14 sf
#4	Device 3	512.50'	<b>0.280 cfs WQ Filters</b> Phase-In= 0.01'

**Primary OutFlow** Max=2.48 cfs @ 8.75 hrs HW=514.02' TW=0.00' (Dynamic Tailwater)

- 1=Culvert (Passes 2.48 cfs of 10.02 cfs potential flow)
- 2=Sharp-Crested Rectangular Weir (Weir Controls 2.48 cfs @ 2.37 fps)

**Secondary OutFlow** Max=0.28 cfs @ 7.70 hrs HW=512.82' TW=0.00' (Dynamic Tailwater)

- 3=Culvert (Passes 0.28 cfs of 0.62 cfs potential flow)
- 4=WQ Filters (Constant Controls 0.28 cfs)



## 20-066 Noyes Subdivision Stormwater Model

Prepared by Branch Engineering

HydroCAD® 10.00-20 s/n 09344 © 2017 HydroCAD Software Solutions LLC

20-066 Noyes Sub  
Type IA 24-hr 10 yr Rainfall=3.20"

Printed 3/9/2021

Page 8

### Summary for Link POST: Post Development

Inflow Area = 734,541 sf, 14.04% Impervious, Inflow Depth = 1.47" for 10 yr event  
Inflow = 2.76 cfs @ 8.75 hrs, Volume= 89,930 cf  
Primary = 2.76 cfs @ 8.75 hrs, Volume= 89,930 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-72.00 hrs, dt= 0.01 hrs

### Summary for Link PRE: Pre Development

Inflow Area = 734,541 sf, 0.48% Impervious, Inflow Depth = 1.22" for 10 yr event  
Inflow = 2.79 cfs @ 8.10 hrs, Volume= 74,959 cf  
Primary = 2.79 cfs @ 8.10 hrs, Volume= 74,959 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-72.00 hrs, dt= 0.01 hrs

## 20-066 Noyes Subdivision Stormwater Model

Prepared by Branch Engineering

HydroCAD® 10.00-20 s/n 09344 © 2017 HydroCAD Software Solutions LLC

20-066 Noyes Sub  
Type IA 24-hr 100 yr Rainfall=4.40"

Printed 3/9/2021

Page 9

Time span=0.00-72.00 hrs, dt=0.01 hrs, 7201 points

Runoff by SBUH method, Split Pervious/Imperv.

Reach routing by Dyn-Stor-Ind method - Pond routing by Dyn-Stor-Ind method

<b>Subcatchment S1: Subdivision</b>	Runoff Area=216,371 sf 46.05% Impervious Runoff Depth=2.94" Tc=10.0 min CN=74/98 Runoff=3.29 cfs 53,018 cf
<b>Subcatchment S2: Offsite</b>	Runoff Area=518,170 sf 0.68% Impervious Runoff Depth=2.31" Tc=30.0 min CN=79/98 Runoff=4.46 cfs 99,551 cf
<b>Subcatchment X1: Subdivision</b>	Runoff Area=216,371 sf 0.00% Impervious Runoff Depth=1.75" Tc=30.0 min CN=72/0 Runoff=1.20 cfs 31,497 cf
<b>Subcatchment X2: Offsite</b>	Runoff Area=518,170 sf 0.68% Impervious Runoff Depth=2.31" Tc=30.0 min CN=79/98 Runoff=4.46 cfs 99,551 cf
<b>Pond 1P: 60" Storage Pipe</b>	Peak Elev=518.46' Storage=15,692 cf Inflow=7.74 cfs 152,569 cf Outflow=7.52 cfs 149,666 cf
<b>Pond UF: Up-Flo</b>	Peak Elev=514.62' Storage=198 cf Inflow=7.52 cfs 149,666 cf Primary=7.24 cfs 124,191 cf Secondary=0.28 cfs 25,379 cf Outflow=7.52 cfs 149,570 cf
<b>Link POST: Post Development</b>	Inflow=7.52 cfs 149,570 cf Primary=7.52 cfs 149,570 cf
<b>Link PRE: Pre Development</b>	Inflow=5.66 cfs 131,048 cf Primary=5.66 cfs 131,048 cf
<b>Total Runoff Area = 1,469,082 sf Runoff Volume = 283,617 cf Average Runoff Depth = 2.32"</b> <b>92.74% Pervious = 1,362,442 sf 7.26% Impervious = 106,640 sf</b>	



**20-066 Noyes Subdivision Stormwater Model**

Prepared by Branch Engineering

HydroCAD® 10.00-20 s/n 09344 © 2017 HydroCAD Software Solutions LLC

20-066 Noyes Sub  
Type IA 24-hr 100 yr Rainfall=4.40"

Printed 3/9/2021

Page 10

**Summary for Subcatchment S1: Subdivision**

Runoff = 3.29 cfs @ 8.00 hrs, Volume= 53,018 cf, Depth= 2.94"

Runoff by SBUH method, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.01 hrs  
Type IA 24-hr 100 yr Rainfall=4.40"

	Area (sf)	CN	Description
*	99,640	98	Impervious
*	116,731	74	Pervious
	216,371	85	Weighted Average
	116,731	74	53.95% Pervious Area
	99,640	98	46.05% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
10.0					Direct Entry,

**Summary for Subcatchment S2: Offsite**

Runoff = 4.46 cfs @ 8.03 hrs, Volume= 99,551 cf, Depth= 2.31"

Runoff by SBUH method, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.01 hrs  
Type IA 24-hr 100 yr Rainfall=4.40"

	Area (sf)	CN	Description
	514,670	79	50-75% Grass cover, Fair, HSG C
*	3,500	98	Existing House
	518,170	79	Weighted Average
	514,670	79	99.32% Pervious Area
	3,500	98	0.68% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
30.0					Direct Entry,

**Summary for Subcatchment X1: Subdivision**

Runoff = 1.20 cfs @ 8.09 hrs, Volume= 31,497 cf, Depth= 1.75"

Runoff by SBUH method, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.01 hrs  
Type IA 24-hr 100 yr Rainfall=4.40"

	Area (sf)	CN	Description
	216,371	72	Woods/grass comb., Good, HSG C
	216,371	72	100.00% Pervious Area

**20-066 Noyes Subdivision Stormwater Model**

Prepared by Branch Engineering

HydroCAD® 10.00-20 s/n 09344 © 2017 HydroCAD Software Solutions LLC

20-066 Noyes Sub  
Type IA 24-hr 100 yr Rainfall=4.40"

Printed 3/9/2021

Page 11

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
30.0					<b>Direct Entry,</b>

**Summary for Subcatchment X2: Offsite**

Runoff = 4.46 cfs @ 8.03 hrs, Volume= 99,551 cf, Depth= 2.31"

Runoff by SBUH method, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.01 hrs  
Type IA 24-hr 100 yr Rainfall=4.40"

Area (sf)	CN	Description
514,670	79	50-75% Grass cover, Fair, HSG C
3,500	98	Existing House
518,170	79	Weighted Average
514,670	79	99.32% Pervious Area
3,500	98	0.68% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
30.0					<b>Direct Entry,</b>

**Summary for Pond 1P: 60" Storage Pipe**

Inflow Area = 734,541 sf, 14.04% Impervious, Inflow Depth = 2.49" for 100 yr event  
 Inflow = 7.74 cfs @ 8.00 hrs, Volume= 152,569 cf  
 Outflow = 7.52 cfs @ 8.05 hrs, Volume= 149,666 cf, Atten= 3%, Lag= 2.8 min  
 Primary = 7.52 cfs @ 8.05 hrs, Volume= 149,666 cf

Routing by Dyn-Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.01 hrs  
 Peak Elev= 518.46' @ 8.05 hrs Surf.Area= 677 sf Storage= 15,692 cf

Plug-Flow detention time= 112.1 min calculated for 149,645 cf (98% of inflow)  
 Center-of-Mass det. time= 99.4 min ( 883.0 - 783.6 )

Volume	Invert	Avail.Storage	Storage Description
#1	513.50'	15,708 cf	<b>60.0" Round Pipe Storage</b> x 4 L= 200.0'

Device	Routing	Invert	Outlet Devices
#1	Primary	513.50'	<b>24.0" Round Culvert</b> L= 50.0' Ke= 0.500 Inlet / Outlet Invert= 513.50' / 513.00' S= 0.0100 ' / ' Cc= 0.900 n= 0.011, Flow Area= 3.14 sf
#2	Device 1	514.70'	<b>2.0" Horiz. Half 2-yr Orifice</b> C= 0.600 Limited to weir flow at low heads
#3	Device 1	516.20'	<b>9.0" Horiz. 10-yr Orifice</b> C= 0.600 Limited to weir flow at low heads
#4	Device 1	517.60'	<b>24.0" Vert. Overflow</b> C= 0.600



## 20-066 Noyes Subdivision Stormwater Model

Prepared by Branch Engineering

HydroCAD® 10.00-20 s/n 09344 © 2017 HydroCAD Software Solutions LLC

20-066 Noyes Sub

Type IA 24-hr 100 yr Rainfall=4.40"

Printed 3/9/2021

Page 12

**Primary OutFlow** Max=7.52 cfs @ 8.05 hrs HW=518.46' TW=514.62' (Dynamic Tailwater)

- ↑ **1=Culvert** (Passes 7.52 cfs of 29.67 cfs potential flow)
- ↑ **2=Half 2-yr Orifice** (Orifice Controls 0.20 cfs @ 9.34 fps)
- ↑ **3=10-yr Orifice** (Orifice Controls 3.20 cfs @ 7.24 fps)
- ↑ **4=Overflow** (Orifice Controls 4.11 cfs @ 3.16 fps)

### Summary for Pond UF: Up-Flo

Inflow Area = 734,541 sf, 14.04% Impervious, Inflow Depth = 2.45" for 100 yr event  
Inflow = 7.52 cfs @ 8.05 hrs, Volume= 149,666 cf  
Outflow = 7.52 cfs @ 8.05 hrs, Volume= 149,570 cf, Atten= 0%, Lag= 0.1 min  
Primary = 7.24 cfs @ 8.05 hrs, Volume= 124,191 cf  
Secondary = 0.28 cfs @ 6.60 hrs, Volume= 25,379 cf

Routing by Dyn-Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.01 hrs

Peak Elev= 514.62' @ 8.05 hrs Surf.Area= 48 sf Storage= 198 cf

Plug-Flow detention time= 2.3 min calculated for 149,549 cf (100% of inflow)

Center-of-Mass det. time= 0.9 min ( 883.9 - 883.0 )

Volume	Invert	Avail.Storage	Storage Description
#1	510.50'	240 cf	<b>Custom Stage Data (Prismatic)</b> Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
510.50	48	0	0
513.50	48	144	144
515.50	48	96	240

Device	Routing	Invert	Outlet Devices
#1	Primary	512.50'	<b>24.0" Round Culvert</b> L= 20.0' Ke= 0.500 Inlet / Outlet Invert= 512.50' / 512.10' S= 0.0200 '/' Cc= 0.900 n= 0.013, Flow Area= 3.14 sf
#2	Device 1	513.50'	<b>2.1' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)
#3	Secondary	512.50'	<b>24.0" Round Culvert</b> L= 20.0' Ke= 0.500 Inlet / Outlet Invert= 512.50' / 512.00' S= 0.0250 '/' Cc= 0.900 n= 0.011, Flow Area= 3.14 sf
#4	Device 3	512.50'	<b>0.280 cfs WQ Filters</b> Phase-In= 0.01'

**Primary OutFlow** Max=7.23 cfs @ 8.05 hrs HW=514.62' TW=0.00' (Dynamic Tailwater)

- ↑ **1=Culvert** (Passes 7.23 cfs of 15.90 cfs potential flow)
- ↑ **2=Sharp-Crested Rectangular Weir** (Weir Controls 7.23 cfs @ 3.45 fps)

**Secondary OutFlow** Max=0.28 cfs @ 6.60 hrs HW=512.78' TW=0.00' (Dynamic Tailwater)

- ↑ **3=Culvert** (Passes 0.28 cfs of 0.49 cfs potential flow)
- ↑ **4=WQ Filters** (Constant Controls 0.28 cfs)

## 20-066 Noyes Subdivision Stormwater Model

Prepared by Branch Engineering

HydroCAD® 10.00-20 s/n 09344 © 2017 HydroCAD Software Solutions LLC

20-066 Noyes Sub

Type IA 24-hr 100 yr Rainfall=4.40"

Printed 3/9/2021

Page 13

### Summary for Link POST: Post Development

Inflow Area = 734,541 sf, 14.04% Impervious, Inflow Depth = 2.44" for 100 yr event  
Inflow = 7.52 cfs @ 8.05 hrs, Volume= 149,570 cf  
Primary = 7.52 cfs @ 8.05 hrs, Volume= 149,570 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-72.00 hrs, dt= 0.01 hrs

### Summary for Link PRE: Pre Development

Inflow Area = 734,541 sf, 0.48% Impervious, Inflow Depth = 2.14" for 100 yr event  
Inflow = 5.66 cfs @ 8.04 hrs, Volume= 131,048 cf  
Primary = 5.66 cfs @ 8.04 hrs, Volume= 131,048 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-72.00 hrs, dt= 0.01 hrs

## 20-066 Noyes Subdivision Stormwater Model

Prepared by Branch Engineering

HydroCAD® 10.00-20 s/n 09344 © 2017 HydroCAD Software Solutions LLC

20-066 Noyes Sub  
Type IA 24-hr Half-2 yr Rainfall=1.10"

Printed 3/9/2021

Page 14

Time span=0.00-72.00 hrs, dt=0.01 hrs, 7201 points

Runoff by SBUH method, Split Pervious/Imperv.

Reach routing by Dyn-Stor-Ind method - Pond routing by Dyn-Stor-Ind method

<b>Subcatchment S1: Subdivision</b>	Runoff Area=216,371 sf 46.05% Impervious Runoff Depth=0.43" Tc=10.0 min CN=74/98 Runoff=0.50 cfs 7,767 cf
<b>Subcatchment S2: Offsite</b>	Runoff Area=518,170 sf 0.68% Impervious Runoff Depth=0.11" Tc=30.0 min CN=79/98 Runoff=0.09 cfs 4,553 cf
<b>Subcatchment X1: Subdivision</b>	Runoff Area=216,371 sf 0.00% Impervious Runoff Depth=0.02" Tc=30.0 min CN=72/0 Runoff=0.02 cfs 445 cf
<b>Subcatchment X2: Offsite</b>	Runoff Area=518,170 sf 0.68% Impervious Runoff Depth=0.11" Tc=30.0 min CN=79/98 Runoff=0.09 cfs 4,553 cf
<b>Pond 1P: 60" Storage Pipe</b>	Peak Elev=515.88' Storage=7,371 cf Inflow=0.51 cfs 12,319 cf Outflow=0.11 cfs 9,417 cf
<b>Pond UF: Up-Flo</b>	Peak Elev=512.63' Storage=102 cf Inflow=0.11 cfs 9,417 cf Primary=0.00 cfs 0 cf Secondary=0.11 cfs 9,321 cf Outflow=0.11 cfs 9,321 cf
<b>Link POST: Post Development</b>	Inflow=0.11 cfs 9,321 cf Primary=0.11 cfs 9,321 cf
<b>Link PRE: Pre Development</b>	Inflow=0.11 cfs 4,997 cf Primary=0.11 cfs 4,997 cf
<b>Total Runoff Area = 1,469,082 sf Runoff Volume = 17,317 cf Average Runoff Depth = 0.14"</b> <b>92.74% Pervious = 1,362,442 sf 7.26% Impervious = 106,640 sf</b>	



**20-066 Noyes Subdivision Stormwater Model**

Prepared by Branch Engineering

HydroCAD® 10.00-20 s/n 09344 © 2017 HydroCAD Software Solutions LLC

20-066 Noyes Sub

Type IA 24-hr Half-2 yr Rainfall=1.10"

Printed 3/9/2021

Page 15

**Summary for Subcatchment S1: Subdivision**

Runoff = 0.50 cfs @ 7.98 hrs, Volume= 7,767 cf, Depth= 0.43"

Runoff by SBUH method, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.01 hrs  
Type IA 24-hr Half-2 yr Rainfall=1.10"

	Area (sf)	CN	Description
*	99,640	98	Impervious
*	116,731	74	Pervious
	216,371	85	Weighted Average
	116,731	74	53.95% Pervious Area
	99,640	98	46.05% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
10.0					Direct Entry,

**Summary for Subcatchment S2: Offsite**

Runoff = 0.09 cfs @ 18.85 hrs, Volume= 4,553 cf, Depth= 0.11"

Runoff by SBUH method, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.01 hrs  
Type IA 24-hr Half-2 yr Rainfall=1.10"

	Area (sf)	CN	Description
	514,670	79	50-75% Grass cover, Fair, HSG C
*	3,500	98	Existing House
	518,170	79	Weighted Average
	514,670	79	99.32% Pervious Area
	3,500	98	0.68% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
30.0					Direct Entry,

**Summary for Subcatchment X1: Subdivision**

Runoff = 0.02 cfs @ 23.01 hrs, Volume= 445 cf, Depth= 0.02"

Runoff by SBUH method, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.01 hrs  
Type IA 24-hr Half-2 yr Rainfall=1.10"

	Area (sf)	CN	Description
	216,371	72	Woods/grass comb., Good, HSG C
	216,371	72	100.00% Pervious Area

**20-066 Noyes Subdivision Stormwater Model**

Prepared by Branch Engineering

HydroCAD® 10.00-20 s/n 09344 © 2017 HydroCAD Software Solutions LLC

20-066 Noyes Sub

Type IA 24-hr Half-2 yr Rainfall=1.10"

Printed 3/9/2021

Page 16

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
30.0					<b>Direct Entry,</b>

**Summary for Subcatchment X2: Offsite**

Runoff = 0.09 cfs @ 18.85 hrs, Volume= 4,553 cf, Depth= 0.11"

Runoff by SBUH method, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.01 hrs  
Type IA 24-hr Half-2 yr Rainfall=1.10"

Area (sf)	CN	Description
514,670	79	50-75% Grass cover, Fair, HSG C
3,500	98	Existing House
518,170	79	Weighted Average
514,670	79	99.32% Pervious Area
3,500	98	0.68% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
30.0					<b>Direct Entry,</b>

**Summary for Pond 1P: 60" Storage Pipe**

Inflow Area = 734,541 sf, 14.04% Impervious, Inflow Depth = 0.20" for Half-2 yr event  
 Inflow = 0.51 cfs @ 7.98 hrs, Volume= 12,319 cf  
 Outflow = 0.11 cfs @ 24.06 hrs, Volume= 9,417 cf, Atten= 78%, Lag= 965.0 min  
 Primary = 0.11 cfs @ 24.06 hrs, Volume= 9,417 cf

Routing by Dyn-Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.01 hrs  
 Peak Elev= 515.88' @ 24.06 hrs Surf.Area= 3,995 sf Storage= 7,371 cf

Plug-Flow detention time= 756.4 min calculated for 9,417 cf (76% of inflow)  
 Center-of-Mass det. time= 615.7 min ( 1,461.6 - 845.9 )

Volume	Invert	Avail.Storage	Storage Description
#1	513.50'	15,708 cf	<b>60.0" Round Pipe Storage</b> x 4 L= 200.0'

Device	Routing	Invert	Outlet Devices
#1	Primary	513.50'	<b>24.0" Round Culvert</b> L= 50.0' Ke= 0.500 Inlet / Outlet Invert= 513.50' / 513.00' S= 0.0100 '/' Cc= 0.900 n= 0.011, Flow Area= 3.14 sf
#2	Device 1	514.70'	<b>2.0" Horiz. Half 2-yr Orifice</b> C= 0.600 Limited to weir flow at low heads
#3	Device 1	516.20'	<b>9.0" Horiz. 10-yr Orifice</b> C= 0.600 Limited to weir flow at low heads
#4	Device 1	517.60'	<b>24.0" Vert. Overflow</b> C= 0.600

**20-066 Noyes Subdivision Stormwater Model**

Prepared by Branch Engineering

HydroCAD® 10.00-20 s/n 09344 © 2017 HydroCAD Software Solutions LLC

20-066 Noyes Sub

Type IA 24-hr Half-2 yr Rainfall=1.10"

Printed 3/9/2021

Page 17

**Primary OutFlow** Max=0.11 cfs @ 24.06 hrs HW=515.88' TW=512.63' (Dynamic Tailwater)

- ↑ **1=Culvert** (Passes 0.11 cfs of 17.76 cfs potential flow)
- ↑ **2=Half 2-yr Orifice** (Orifice Controls 0.11 cfs @ 5.23 fps)
- ↑ **3=10-yr Orifice** ( Controls 0.00 cfs)
- ↑ **4=Overflow** ( Controls 0.00 cfs)

**Summary for Pond UF: Up-Flo**

Inflow Area = 734,541 sf, 14.04% Impervious, Inflow Depth > 0.15" for Half-2 yr event  
 Inflow = 0.11 cfs @ 24.06 hrs, Volume= 9,417 cf  
 Outflow = 0.11 cfs @ 24.07 hrs, Volume= 9,321 cf, Atten= 0%, Lag= 0.5 min  
 Primary = 0.00 cfs @ 0.00 hrs, Volume= 0 cf  
 Secondary = 0.11 cfs @ 24.07 hrs, Volume= 9,321 cf

Routing by Dyn-Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.01 hrs

Peak Elev= 512.63' @ 24.07 hrs Surf.Area= 48 sf Storage= 102 cf

Plug-Flow detention time= 24.9 min calculated for 9,321 cf (99% of inflow)

Center-of-Mass det. time= 10.5 min ( 1,472.1 - 1,461.6 )

Volume	Invert	Avail.Storage	Storage Description
#1	510.50'	240 cf	<b>Custom Stage Data (Prismatic)</b> Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
510.50	48	0	0
513.50	48	144	144
515.50	48	96	240

Device	Routing	Invert	Outlet Devices
#1	Primary	512.50'	<b>24.0" Round Culvert</b> L= 20.0' Ke= 0.500 Inlet / Outlet Invert= 512.50' / 512.10' S= 0.0200 '/' Cc= 0.900 n= 0.013, Flow Area= 3.14 sf
#2	Device 1	513.50'	<b>2.1' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)
#3	Secondary	512.50'	<b>24.0" Round Culvert</b> L= 20.0' Ke= 0.500 Inlet / Outlet Invert= 512.50' / 512.00' S= 0.0250 '/' Cc= 0.900 n= 0.011, Flow Area= 3.14 sf
#4	Device 3	512.50'	<b>0.280 cfs WQ Filters</b> Phase-In= 0.01'

**Primary OutFlow** Max=0.00 cfs @ 0.00 hrs HW=510.50' TW=0.00' (Dynamic Tailwater)

- ↑ **1=Culvert** ( Controls 0.00 cfs)
- ↑ **2=Sharp-Crested Rectangular Weir** ( Controls 0.00 cfs)

**Secondary OutFlow** Max=0.11 cfs @ 24.07 hrs HW=512.63' TW=0.00' (Dynamic Tailwater)

- ↑ **3=Culvert** (Inlet Controls 0.11 cfs @ 1.25 fps)
- ↑ **4=WQ Filters** (Passes 0.11 cfs of 0.28 cfs potential flow)



## 20-066 Noyes Subdivision Stormwater Model

Prepared by Branch Engineering

HydroCAD® 10.00-20 s/n 09344 © 2017 HydroCAD Software Solutions LLC

20-066 Noyes Sub

Type IA 24-hr Half-2 yr Rainfall=1.10"

Printed 3/9/2021

Page 18

### Summary for Link POST: Post Development

Inflow Area = 734,541 sf, 14.04% Impervious, Inflow Depth > 0.15" for Half-2 yr event  
Inflow = 0.11 cfs @ 24.07 hrs, Volume= 9,321 cf  
Primary = 0.11 cfs @ 24.07 hrs, Volume= 9,321 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-72.00 hrs, dt= 0.01 hrs

### Summary for Link PRE: Pre Development

Inflow Area = 734,541 sf, 0.48% Impervious, Inflow Depth = 0.08" for Half-2 yr event  
Inflow = 0.11 cfs @ 19.84 hrs, Volume= 4,997 cf  
Primary = 0.11 cfs @ 19.84 hrs, Volume= 4,997 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-72.00 hrs, dt= 0.01 hrs

## 20-066 Noyes Subdivision Stormwater Model

Prepared by Branch Engineering

HydroCAD® 10.00-20 s/n 09344 © 2017 HydroCAD Software Solutions LLC

20-066 Noyes Sub  
Type IA 24-hr WQ Rainfall=1.38"

Printed 3/9/2021

Page 19

Time span=0.00-72.00 hrs, dt=0.01 hrs, 7201 points

Runoff by SBUH method, Split Pervious/Imperv.

Reach routing by Dyn-Stor-Ind method - Pond routing by Dyn-Stor-Ind method

<b>Subcatchment S1: Subdivision</b>	Runoff Area=216,371 sf 46.05% Impervious Runoff Depth=0.59" Tc=10.0 min CN=74/98 Runoff=0.65 cfs 10,714 cf
<b>Subcatchment S2: Offsite</b>	Runoff Area=518,170 sf 0.68% Impervious Runoff Depth=0.21" Tc=30.0 min CN=79/98 Runoff=0.17 cfs 9,142 cf
<b>Subcatchment X1: Subdivision</b>	Runoff Area=216,371 sf 0.00% Impervious Runoff Depth=0.08" Tc=30.0 min CN=72/0 Runoff=0.04 cfs 1,456 cf
<b>Subcatchment X2: Offsite</b>	Runoff Area=518,170 sf 0.68% Impervious Runoff Depth=0.21" Tc=30.0 min CN=79/98 Runoff=0.17 cfs 9,142 cf
<b>Pond 1P: 60" Storage Pipe</b>	Peak Elev=516.27' Storage=8,943 cf Inflow=0.69 cfs 19,856 cf Outflow=0.28 cfs 16,953 cf
<b>Pond UF: Up-Flo</b>	Peak Elev=512.96' Storage=118 cf Inflow=0.28 cfs 16,953 cf Primary=0.00 cfs 0 cf Secondary=0.28 cfs 16,857 cf Outflow=0.28 cfs 16,857 cf
<b>Link POST: Post Development</b>	Inflow=0.28 cfs 16,857 cf Primary=0.28 cfs 16,857 cf
<b>Link PRE: Pre Development</b>	Inflow=0.20 cfs 10,598 cf Primary=0.20 cfs 10,598 cf

**Total Runoff Area = 1,469,082 sf Runoff Volume = 30,453 cf Average Runoff Depth = 0.25"**  
**92.74% Pervious = 1,362,442 sf 7.26% Impervious = 106,640 sf**

**20-066 Noyes Subdivision Stormwater Model**

Prepared by Branch Engineering

HydroCAD® 10.00-20 s/n 09344 © 2017 HydroCAD Software Solutions LLC

20-066 Noyes Sub  
Type IA 24-hr WQ Rainfall=1.38"

Printed 3/9/2021

Page 20

**Summary for Subcatchment S1: Subdivision**

Runoff = 0.65 cfs @ 7.97 hrs, Volume= 10,714 cf, Depth= 0.59"

Runoff by SBUH method, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.01 hrs  
Type IA 24-hr WQ Rainfall=1.38"

	Area (sf)	CN	Description
*	99,640	98	Impervious
*	116,731	74	Pervious
	216,371	85	Weighted Average
	116,731	74	53.95% Pervious Area
	99,640	98	46.05% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
10.0					Direct Entry,

**Summary for Subcatchment S2: Offsite**

Runoff = 0.17 cfs @ 17.04 hrs, Volume= 9,142 cf, Depth= 0.21"

Runoff by SBUH method, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.01 hrs  
Type IA 24-hr WQ Rainfall=1.38"

	Area (sf)	CN	Description
	514,670	79	50-75% Grass cover, Fair, HSG C
*	3,500	98	Existing House
	518,170	79	Weighted Average
	514,670	79	99.32% Pervious Area
	3,500	98	0.68% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
30.0					Direct Entry,

**Summary for Subcatchment X1: Subdivision**

Runoff = 0.04 cfs @ 20.41 hrs, Volume= 1,456 cf, Depth= 0.08"

Runoff by SBUH method, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.01 hrs  
Type IA 24-hr WQ Rainfall=1.38"

	Area (sf)	CN	Description
	216,371	72	Woods/grass comb., Good, HSG C
	216,371	72	100.00% Pervious Area



**20-066 Noyes Subdivision Stormwater Model**

Prepared by Branch Engineering

HydroCAD® 10.00-20 s/n 09344 © 2017 HydroCAD Software Solutions LLC

20-066 Noyes Sub  
Type IA 24-hr WQ Rainfall=1.38"

Printed 3/9/2021

Page 21

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
30.0					<b>Direct Entry,</b>

**Summary for Subcatchment X2: Offsite**

Runoff = 0.17 cfs @ 17.04 hrs, Volume= 9,142 cf, Depth= 0.21"

Runoff by SBUH method, Split Pervious/Imperv., Time Span= 0.00-72.00 hrs, dt= 0.01 hrs  
Type IA 24-hr WQ Rainfall=1.38"

Area (sf)	CN	Description
514,670	79	50-75% Grass cover, Fair, HSG C
3,500	98	Existing House
518,170	79	Weighted Average
514,670	79	99.32% Pervious Area
3,500	98	0.68% Impervious Area

Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
30.0					<b>Direct Entry,</b>

**Summary for Pond 1P: 60" Storage Pipe**

Inflow Area = 734,541 sf, 14.04% Impervious, Inflow Depth = 0.32" for WQ event  
 Inflow = 0.69 cfs @ 8.00 hrs, Volume= 19,856 cf  
 Outflow = 0.28 cfs @ 17.06 hrs, Volume= 16,953 cf, Atten= 59%, Lag= 543.5 min  
 Primary = 0.28 cfs @ 17.06 hrs, Volume= 16,953 cf

Routing by Dyn-Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.01 hrs  
 Peak Elev= 516.27' @ 17.06 hrs Surf.Area= 3,976 sf Storage= 8,943 cf

Plug-Flow detention time= 627.7 min calculated for 16,950 cf (85% of inflow)  
 Center-of-Mass det. time= 540.7 min ( 1,389.5 - 848.7 )

Volume	Invert	Avail.Storage	Storage Description
#1	513.50'	15,708 cf	<b>60.0" Round Pipe Storage</b> x 4 L= 200.0'

Device	Routing	Invert	Outlet Devices
#1	Primary	513.50'	<b>24.0" Round Culvert</b> L= 50.0' Ke= 0.500 Inlet / Outlet Invert= 513.50' / 513.00' S= 0.0100 ' /' Cc= 0.900 n= 0.011, Flow Area= 3.14 sf
#2	Device 1	514.70'	<b>2.0" Horiz. Half 2-yr Orifice</b> C= 0.600 Limited to weir flow at low heads
#3	Device 1	516.20'	<b>9.0" Horiz. 10-yr Orifice</b> C= 0.600 Limited to weir flow at low heads
#4	Device 1	517.60'	<b>24.0" Vert. Overflow</b> C= 0.600

## 20-066 Noyes Subdivision Stormwater Model

Prepared by Branch Engineering

HydroCAD® 10.00-20 s/n 09344 © 2017 HydroCAD Software Solutions LLC

20-066 Noyes Sub  
Type IA 24-hr WQ Rainfall=1.38"

Printed 3/9/2021

Page 22

**Primary OutFlow** Max=0.28 cfs @ 17.06 hrs HW=516.27' TW=512.81' (Dynamic Tailwater)

- ↑ **1=Culvert** (Passes 0.28 cfs of 20.14 cfs potential flow)
- ↑ **2=Half 2-yr Orifice** (Orifice Controls 0.13 cfs @ 6.04 fps)
- ↑ **3=10-yr Orifice** (Weir Controls 0.15 cfs @ 0.88 fps)
- ↑ **4=Overflow** ( Controls 0.00 cfs)

### Summary for Pond UF: Up-Flo

Inflow Area = 734,541 sf, 14.04% Impervious, Inflow Depth > 0.28" for WQ event  
Inflow = 0.28 cfs @ 17.06 hrs, Volume= 16,953 cf  
Outflow = 0.28 cfs @ 16.80 hrs, Volume= 16,857 cf, Atten= 1%, Lag= 0.0 min  
Primary = 0.00 cfs @ 0.00 hrs, Volume= 0 cf  
Secondary = 0.28 cfs @ 16.80 hrs, Volume= 16,857 cf

Routing by Dyn-Stor-Ind method, Time Span= 0.00-72.00 hrs, dt= 0.01 hrs  
Peak Elev= 512.96' @ 18.06 hrs Surf.Area= 48 sf Storage= 118 cf

Plug-Flow detention time= 15.3 min calculated for 16,854 cf (99% of inflow)  
Center-of-Mass det. time= 6.0 min ( 1,395.4 - 1,389.5 )

Volume	Invert	Avail.Storage	Storage Description
#1	510.50'	240 cf	<b>Custom Stage Data (Prismatic)</b> Listed below (Recalc)

Elevation (feet)	Surf.Area (sq-ft)	Inc.Store (cubic-feet)	Cum.Store (cubic-feet)
510.50	48	0	0
513.50	48	144	144
515.50	48	96	240

Device	Routing	Invert	Outlet Devices
#1	Primary	512.50'	<b>24.0" Round Culvert</b> L= 20.0' Ke= 0.500 Inlet / Outlet Invert= 512.50' / 512.10' S= 0.0200 '/' Cc= 0.900 n= 0.013, Flow Area= 3.14 sf
#2	Device 1	513.50'	<b>2.1' long Sharp-Crested Rectangular Weir</b> 2 End Contraction(s)
#3	Secondary	512.50'	<b>24.0" Round Culvert</b> L= 20.0' Ke= 0.500 Inlet / Outlet Invert= 512.50' / 512.00' S= 0.0250 '/' Cc= 0.900 n= 0.011, Flow Area= 3.14 sf
#4	Device 3	512.50'	<b>0.280 cfs WQ Filters</b> Phase-In= 0.01'

**Primary OutFlow** Max=0.00 cfs @ 0.00 hrs HW=510.50' TW=0.00' (Dynamic Tailwater)

- ↑ **1=Culvert** ( Controls 0.00 cfs)
- ↑ **2=Sharp-Crested Rectangular Weir** ( Controls 0.00 cfs)

**Secondary OutFlow** Max=0.28 cfs @ 16.80 hrs HW=512.75' TW=0.00' (Dynamic Tailwater)

- ↑ **3=Culvert** (Passes 0.28 cfs of 0.39 cfs potential flow)
- ↑ **4=WQ Filters** (Constant Controls 0.28 cfs)

## 20-066 Noyes Subdivision Stormwater Model

Prepared by Branch Engineering

HydroCAD® 10.00-20 s/n 09344 © 2017 HydroCAD Software Solutions LLC

20-066 Noyes Sub  
Type IA 24-hr WQ Rainfall=1.38"

Printed 3/9/2021

Page 23

### Summary for Link POST: Post Development

Inflow Area = 734,541 sf, 14.04% Impervious, Inflow Depth > 0.28" for WQ event  
Inflow = 0.28 cfs @ 16.80 hrs, Volume= 16,857 cf  
Primary = 0.28 cfs @ 16.80 hrs, Volume= 16,857 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-72.00 hrs, dt= 0.01 hrs

### Summary for Link PRE: Pre Development

Inflow Area = 734,541 sf, 0.48% Impervious, Inflow Depth = 0.17" for WQ event  
Inflow = 0.20 cfs @ 17.88 hrs, Volume= 10,598 cf  
Primary = 0.20 cfs @ 17.88 hrs, Volume= 10,598 cf, Atten= 0%, Lag= 0.0 min

Primary outflow = Inflow, Time Span= 0.00-72.00 hrs, dt= 0.01 hrs